

# EZ ZONE™ Tape

**PURGE GAS RETAINING TAPE**

**FOR A CONTAMINANT-FREE WELD**




**EZ Zone™ Tape is a purge gas retaining tape used to seal the root gap between pipes to trap Argon gas, but in a most innovative way!**

- Clean Contaminant-Free Welding
- Halogen and Fluorocarbon Free
- High temperature resistant
- Reduces pipe clean up time
- Reduces amount of gas used
- Improve the safety of your workplace


## How EZ Zone™ Tape Works

### Attributes:



Composed of two adhesive sections separated by an adhesive-free center "zone."

### Application:



The adhesive edges stick to the area surrounding the root gap on stainless steel and aluminum pipes with the adhesive free "zone" being placed over the weld.

### Result:



Adhesive never comes in contact with the weld joint as it is welded, creating a clean, contaminant-free weld.

\*US and Foreign Patents Pending



### Also Available: EZ Tape™

- High temperature resistant, fully coated aluminum tape
- For capping pipe ends during transport
- Controls release of gas by sealing root gap
- For other conventional uses in the field such as heating, air conditioning, refrigeration and acting as a vapor barrier

# EZ ZONE™ Tape

## PURGE GAS RETAINING TAPE

### FOR A CONTAMINANT-FREE WELD

#### Description

A 3 mil (75 micron) aluminum foil coated with a high shear, high heat-resistant acrylic adhesive system. The soft foil conforms well to irregular surfaces.

#### Specifications for Aluminum Welding Tape

| Item                     | Item Number | Width        | Adhesive Free "ZONE" Width | Length    |
|--------------------------|-------------|--------------|----------------------------|-----------|
| EZ ZONE™ TAPE            | EZ-ZT2.5    | 2.5" (64mm)  | 1"                         | 75' (23m) |
| EZ ZONE™ TAPE            | EZ-ZT4.0    | 4.0" (102mm) | 2"                         | 75' (23m) |
| EZ TAPE™<br>Fully-coated | EZ-T2.0     | 2.0" (51mm)  | N/A                        | 75' (23m) |

Custom sizes available upon request.

\*US and Foreign Patents Pending

|                                   |               |       |         |
|-----------------------------------|---------------|-------|---------|
| ▶ Heat Resistance:                | Adhesive      | 425°F | 219°C   |
|                                   | Aluminum Tape | 595°F | 313°C   |
| ▶ Minimum Application Temperature |               | 10°F  | -12.5°C |

*EZ Zone™ Tape was selected to be used at an Australian LNG site.*



*In a short period of time, EZ Zone™ Tape has become a standard in the nuclear, chemical, aerospace and other industries.*

For additional product information, quotations and ordering, please contact:

#### **Aquasol Corporation**

80 Thompson Street  
North Tonawanda, NY 14120 USA  
1-800-564-WELD (9353)  
Phone 716.564.8888  
Fax 716.564.8889  
Email: info@aquasolcorporation.com  
www.aquasolcorporation.com

DISTRIBUTED BY: