



Simply better.

# BESSEY® C Clamps

540 Series Ductile Alloy & 400 Series Drop Forged C-Clamps

## Features & Benefits

- **NEW** 540 series C-clamps made of high tensile ductile alloy casting provides excellent strength in a cast clamp
- Black oxide spindle to resist corrosion



## **NEW** 540 Series Ductile Alloy C-Clamps

Catalog Number	Throat Depth	Clamping Capacity	Spindle Diameter	Nominal Load Test
540 - 2-1/2	1 3/4"	0 - 2 1/2"	1/2"	1100 lbs
540 - 3	1 7/8"	0 - 3"	1/2"	1800 lbs
540 - 4	2 1/16"	0 - 4"	5/8"	2150 lbs
540 - 5	2 1/2"	0 - 5"	5/8"	2250 lbs
540 - 6	2 3/4"	0 - 6"	5/8"	2450 lbs
540 - 8	3 1/4"	0 - 8"	3/4"	2750 lbs
540 - 10	3 5/8"	0 - 10"	7/8"	2850 lbs
540 - 12	3 5/8"	0 - 12"	7/8"	2850 lbs
540 - 14	3 3/4"	0 - 14"	7/8"	2850 lbs

## Features & Benefits

- Drop forged and heat-treated for added strength
- Ball-joint swivel pad
- Available in two styles:
  - Copper coated to resist weld spatter
  - Black oxide to resist corrosion
- Large Acme threads for faster clamping



## 400 Series Drop Forged C-Clamps

Catalog Number	Throat Depth	Clamping Capacity	Spindle Diameter	Nominal Load Test
<b>HiVis frame &amp; copper coated spindle</b>				
CDF402CHV	2"	0 - 2"	1/2"	3500 lbs
CDF403CHV	2 3/8"	0 - 3"	1/2"	3500 lbs
CDF404CHV	2 3/4"	0 - 4"	3/4"	6200 lbs
CDF406CHV	3 5/8"	0 - 6"	3/4"	6900 lbs
CDF408CHV	4 1/2"	0 - 8"	3/4"	6900 lbs
CDF410CHV	5 3/8"	2 - 10"	3/4"	8000 lbs
CDF412CHV	5 3/4"	2 - 12"	3/4"	9300 lbs
<b>Black frame &amp; black spindle</b>				
CDF402	2"	0 - 2"	1/2"	3500 lbs
CDF403	2 3/8"	0 - 3"	1/2"	3500 lbs
CDF404	2 3/4"	0 - 4"	3/4"	6200 lbs
CDF406	3 5/8"	0 - 6"	3/4"	6900 lbs
CDF408	4 1/2"	0 - 8"	3/4"	6900 lbs
CDF410	5 3/8"	2 - 10"	3/4"	8000 lbs
CDF412	5 3/4"	2 - 12"	3/4"	9300 lbs